Discover® MIXTECHEGM

14

(10)

THE MOST SIGNIFICANT IMPROVEMENT IN A BATTERY IN 50 YEARS.

MIXTECH - 360° Acid Mixing Technology

- Eliminates acid stratification
- Minimizes sulphation preventing premature capacity loss
- Ensures uniform material utilization guaranteeing longer high
- performance life
 Maintains Dynatmic Charge Acceptance essential for highly equipped vehicles with intense driving schedules
- Delivers longer battery life in extreme temperatures

88 00 00 Di

Thick Enhanced Negative Grids with increased active material density and Carbon additives improve plate strength, cycle life and Dynamic Charge Acceptance delivering a significant reduction in charge time.

Fiber-lock Scrim reduces active material erosion on positive and negative plate

Envelope (+) Non-woven AGM Separators

- Reduces internal resistance and promotes quicker recharging ability
- Maximises cell compression requirements and reduces plate shedding
- Provides 3x the cyclic stability and 10x the vibration resistance of conventional batteries

Thick Enhanced Calcium / High Tin Positive Grids

- Provide improved corrosion resistance and life in deep cycle/starting applications
- Increase strength and Super Heavy Duty reliability

 $NaSO_{4}$ Sodium Sulphate additives improve the cycle life, charge acceptance and maintenance-free operations



4

5

5

Thick Positive Grids with increased active material, additives and high red lead content increase initial capacity and active material bonds, promote high sustained voltages under heavy cranking loads and improve deep cycle performance and life

4



Element Bonding provides vibration resistance and helps to resist positive plate growth



Reinforced Polypropylene Case utilizes completely sealed cover for true maintenance free performance



Integrated carry handles



Central Degassing manifold with integrated flame arrestors collect and discharge gas away from terminals improving safety and reducing terminal corrosion. Gasses travel through a spider-web like maze within the manifold trapping the water and electrolyte vapors re-combining them back into the battery preventing premature dry out.



3/8" stainless stud or cold forged SAE terminals



Anchor Bonding provides plate stability and shock related vibration resistance

Highly Compressed Cell Groups increase cranking performance & vibration resistance