

VRLA AGM

FLOAT STANDBY

Discover® VRLA AGM Float and Standby batteries are maintenance-free and deliver high reliability in general purpose applications such as toys, medical devices, broadband, cableTV, fire, security systems and emergency lighting.



EXTENDED
SERVICE LIFE



EXTREME
TEMPERATURES



RELIABLE, SAFE,
CERTIFIED

Part No.	Volts	C20	C10	C5	C1	Length	Width	Height*	Weight	Terminal
						(mm)			(kg)	
VRLA AGM FLOAT STANDBY										
D21000	2	110	100	88	65	171	72	206	5.60	F10M8
D25000	2	540	500	440	300	241	175	330	31.00	F10M8
D210000	2	1075	1000	890	615	475	175	330	61.00	F10M8
D215000	2	1615	1500	1340	920	400	350	345	94.00	F10M8
D220000	2	2150	2000	1790	1230	490	350	345	123.00	F10M8
D225000	2	2690	2500	2250	1520	490	350	345	140.00	F10M8
D230000	2	3225	3000	2675	1850	710	350	345	190.00	F10M8
D260	2	6	5.5	5.2	3.6	51	33	99	0.36	F1
D445S	4	4.5	4.3	3.9	2.8	48	52	94	0.52	F1
D4100	4	10	9.2	8	6.2	102	44	95	0.95	F1
D613	6	1.3	1.1	1.05	0.78	97	24	52	0.30	F1
D613W	6	1.3	1.1	1.05	0.78	97	24	52	0.31	T21
D620	6	2	1.8	1.7	1.3	43	37	76	0.34	F1 / T5
D628	6	2.8	2.6	2.3	1.85	66	33	97	0.55	F1
D632	6	3.2	3	2.8	1.95	134	35	61	0.62	F1
D645	6	4.5	4.3	3.9	2.8	70	47	101	0.75	F1
D645S	6	4.6	4.4	4.2	3.1	67	67	96	0.80	SP
D670	6	7	6.6	6	4.3	151	34	94	1.08	F1 / F2
D672	6	7.2	6.8	6.2	4.5	151	34	94	1.10	F1 / F2
D680S	6	8	7.6	6.9	4.9	98	56	117	1.25	F1 / F2
D6120	6	12	11.4	10.2	7.5	151	50	94	1.75	F1 / F2
D6140T	6	14	13.5	13	9.8	108	71	140	2.30	FC
D61800	6	190	180	155	110	306	168	220	25.00	F11M6 / F12M8
D1208	12	0.8	0.76	0.68	0.52	96	25	62	0.36	T9 / T13
D1213	12	1.3	1.15	1.1	0.81	97	43	52	0.56	F1
D1223	12	2.3	2	1.95	1.46	178	35	61	0.95	F1
D1226	12	2.6	2.5	2.4	1.95	178	35	61	1.00	F1
D1232	12	3.2	3	2.9	1.95	134	67	61	1.17	F1
D1235	12	3.5	3.3	3.1	2.3	134	67	61	1.32	F1
D1245	12	4.5	4.3	3.9	2.8	90	70	101	1.52	F1/F2

VRLA AGM

FLOAT STANDBY



EXTENDED
SERVICE LIFE



EXTREME
TEMPERATURES



RELIABLE, SAFE,
CERTIFIED

Part No.	Volts	C20	C10	C5	C1	Length	Width	Height*	Weight	Terminal
						(mm)			(kg)	
D1250	12	5	4.7	4.3	3.2	90	70	101	1.62	F1/F2
D1255	12	5.5	5.2	4.8	3.8	90	70	101	1.56	F1/F2
D1270	12	7	6.6	6	4.3	151	65	95	2.06	F1/F2
D1272	12	7.2	6.8	6.2	4.5	151	65	95	2.15	F1/F2
D1275	12	7.5	7.1	6.5	4.7	151	65	95	2.20	F1/F2
D1280	12	8	7.6	6.9	5	151	65	95	2.25	F1/F2
D1290	12	9	8.5	7.7	5.8	151	65	95	2.45	F1/F2
D12100S	12	10	9.5	8.5	6	151	65	111	2.90	F1/F2
D12120	12	12	11.4	10.2	7.5	151	98	95	3.50	F1/F2
D12140	12	14	13.3	12	9.5	151	98	95	3.75	F2
D12150	12	15	14.4	13	9.8	181	77	167	5.05	F3S/F3R/F13M5
D12180	12	18	16.2	14.5	11	181	77	167	5.16	F3S/F3R/F4/F13M5
D12200	12	20	17.5	17	14	181	77	167	5.52	F3S/F3R/F4/F13M5
D12220	12	22	21	18.7	15	181	77	167	6.15	F3S/F3R/F4/F13M5
D12240	12	24	23	20.5	15	166	175	125	7.50	F3S/F3R/F4/F13M5
D12260	12	26	24	22.3	15.8	166	175	125	7.75	F3S/F3R/F4/F13M5
D12280P	12	28	27	24	20.5	165	125	175	9.00	F6 / F13M5
D12350	12	35	33	28.5	20	195	130	155	9.70	F7 / F11M6
D12400	12	42	40	34	25	197	165	170	12.20	F4 / F11M6
D12450	12	48	45	38.5	28	197	165	170	13.25	F4 / F11M6
D12550	12	58	55	48	35	229	138	208	16.00	F5 / F11M6
D12650S	12	67	65	55.5	39.5	350	167	179	19.60	F5 / F11M6
D12700	12	74	70	60	42	260	169	208	19.60	F9 / F11M6
D12750	12	77	75	67.5	48.5	260	169	208	22.40	F9 / F11M6
D12800S	12	84	80	69	50	350	167	179	23.00	F11M6 / F5
D12900	12	100	90	81	61	306	169	208	26.40	F11M6/F17/F12M8
D121000	12	104	100	89	75	328	171	214	30.50	F5
D121200S	12	128	122	100.5	87	410	176	228	35.50	F12M8
D121350	12	140	135	121	92	341	173	283	40.00	F12M8
D121500	12	156	150	134	106	482	170	242	45.00	F12M8 / F5
D121800	12	186	180	160	115	522	238	218	56.00	F12M8 / F16
D122000	12	210	200	186	135	522	238	218	58.80	F12M8 / F16
D122400	12	250	240	204	152	520	268	220	66.00	F12M8
D122600	12	270	260	225	168	520	269	220	71.00	F12M8

* Height refers to the distance from the bottom to the top of the case, and does not include the terminals.

VRLA AGM

FLOAT STANDBY



EXTENDED SERVICE LIFE

- Long Life Superior to Flooded Lead-Acid Batteries.
- 99% Gas Recombination Extends Life.



EXTREME TEMPERATURES

- Wide Ambient Operating Temperature.



RELIABLE, SAFE, CERTIFIED

- Sealed Valve Regulated AGM
- Maintenance-Free
- Nonspillable, No-Gas
- Safe for Environmentally Sensitive Areas
- Flame Retardant ABS Case and Cover with UL94 V0 Rating Available.

