

VRLA AGM





HIGH RATE

Discover® VRLA AGM High Rate batteries are maintenance-free and deliver high rate backup for UPS and critical power applications.



Part No.	Volts	Watts per Cell 15-min	C20	C10	C1	Length	Width	Height*	Weight	Terminal
						(mm)			(kg)	
VRLA AGM HIGH RATE										
D12-22W	12	22	5.4	4.8	4	90	70	101	1.63	F2
D12-37W	12	37	9	8.5	6.84	151	65	93	2.55	F2
D12-92W	12	92	21.5	20	17.5	181	77	167	6.25	F13M5
D12-120W	12	120	30	27	23	165	125	175	8.80	F13M5
D12-150W	12	150	34	32	26	195	130	155	10.60	F11M6
D12-250W	12	250	57	55	48	229	138	208	17.85	F11M6
D12-300W	12	302	78	75	56	260	169	208	24.10	F11M6
D12-350W	12	355	94	90	67	306	169	208	28.50	F21M6
D12-420W	12	420	118	113	80	328	171	214	31.60	F11M6
D12-520W	12	520	143	138	103	341	173	283	43.50	F11M6

* Height refers to the distance from the bottom to the top of the case, and does not include the terminals.



ENHANCED RUN TIME

- Consistent amp hour capacity over lifetime
- Superior high-rate discharge performance



EXTENDED SERVICE LIFE

- 5-10 year design life in short duration backup power
- Low self-discharge rates prolongs shelf life
- 99% gas recombination extends life



EXTREME TEMPERATURES

- Wide ambient operating temperature
- Low temperature operation superior to flooded/Gel batteries



RELIABLE, SAFE, CERTIFIED

- Valve Regulated Lead-Acid, AGM
- Maintenance-free, nonspillable, no-gassing
- Flame retardant (UL94:V0) ABS case and cover available